

Peelers and strippers for cable preparation

Part Number	Description
36-060	Flexi-Peeler™ round cable stripper , for cable diameters 4.5 to 40 mm, precisely cuts jacket with rotary, straight lengthwise and spiral cuts, cut depth is adjustable
36-061	Replacement blade , for both versions
36-177	Sock Slicer braid cutter , specially designed for fast, easy braid removal. The protected blade cannot nick conductors and can be repositioned for optimum sharpness should it ever get dull.
36-146	Super Peeler round cable stripper , for cable diameters 19 to 32 mm
36-147	Super Peeler round cable stripper , for cable diameters 32 to 51 mm
36-148	Replacement blade for Super Peeler, for both versions
36-135-M1	FCJ flat cable stripper , for flat cables
36-138	Replacement blades for FCJ stripper, six per pack
36-139-M1	Replacement blade guide , for FCJ stripper
37-177	Wire stripper , for 0.5 mm ² to 1.0 mm ²
36-219	Automatic wire stripper , for 0.5 mm ² to 4.0 mm ²
36-220	Replacement blades , for 36-219 automatic wire stripper, one pair

36-060



36-177




36-146



36-135-M1



37-177



Cutters, crimpers and gauges

Part Number	Description
36-178	Steel core cutters, high-leverage cutters with Swiss-made carbide steel blades to cut steel reinforcement cable found in traveling cables
WR-IMPACT	Impact-style wire rope cutter, Morse-Starrett 101 for wire rope up to 19 mm dia.
WR-HYDRAULIC	Hydraulic-style wire rope cutter, Morse-Starrett W075 for wire rope up to 19 mm dia.
WR-RATCHET	Ratchet-style wire rope cutter, Cooper Tools 8690 TN for wire rope up to 19 mm dia.
WR-MT-METRIC	Wire rope measuring tool, conveniently-sized tool for quick and accurate measurement of rope diameters. If the rope fits in the groove or a rope with rough fits in the step groove, retire the rope.
36-097	Crimping tool
36-143	Swaging tool
36-145	Ferrules and stops, 2 mm, 2 ferrules/2 stops
36-144	Ferrules and stops, 3 mm, 2 ferrules/2 stops

36-219



36-178



WR-IMPACT



WR-HYDRAULIC



WR-RATCHET



Wire management

Part Number	Description
36-221	Hand wire caddy
36-222	Reel roller, for up to 76 cm reels

WR-MT-METRIC




36-097



36-221



36-143



36-222



Tools



Conduit and flex tools

Part Number	Description
36-002	Conduit bender, for 13 mm, 10 cm inside bending radius
36-001	Conduit bender, for 19 mm, 12.5 cm inside bending radius
36-000	Conduit bender, for 25 mm, 15 cm inside bending radius
36-214	Conduit bender, for 32 mm, 23 cm inside bending radius
Conduit benders are strong, light aluminum construction. They have a precision located degree scale, star, arrow and rim notch for perfect bends every time.	
36-217	Flex conduit cutter, for 9.5, 13 and 16 mm flex conduit
36-218	Replacement blade, one



Specialty tools and materials

Part Number	Description
MIS-050	Flat flex rail file, 35 cm long, 3 teeth/cm.
MIS-050A	File holder, for MIS-050
MIS-111	Contact burnishing tools, 76 mm long x 5 mm wide x 0.17 mm thick, leaves no residue, insulated plastic handle
MIS-112	Heavy duty contact burnishing tools, 82 mm long x 5 mm wide x 0.25 mm thick, leaves no residue, insulated plastic handle
MIS-126A	Security screwdriver, magnetic holder, handle holds spanner bits #6, #8, #10 and phillips bit
MIS-186A	Brush seater/commutator cleaning stone, medium-soft grade stone, for general purpose use, additional sizes and grades available
MIS-211	Door pressure gauge
MIS-211A	Hydraulic pressure gauge, 0.6 m hose, 70 BAR, quick-connect coupling, flexible hose, liquid-filled easy-to-read gauge
WMT-2	Thrust bearing tool, for Westinghouse #28 and #38 machines
WF-STRP	Compensation cable strip kit, with instructions, gloves, hacksaw, nippers, PVC pipe cutters, utility knife, angle bracket (already assembled), clamps for all Draka compensation cables and carrying case



Multimeters and AC/DC clamp-on meters

Part Number	Description
MIS-MTR-001	Extech model EX-410 meter, DMM functions and features, Cat 3 600V rated, VDC accuracy to 0.50%, temperature (type K), 2000 counts, backlit display, data hold, auto power off, input alert, CE/UL certified, one year warranty
MIS-MTR-003	Extech model EX-470 infrared thermometer, with laser, Cat 3 600V rated, VDC accuracy to 0.30%, temperature (type K and infrared), capacitance and frequency, 4000 counts, true RMS, autoranging, backlit display, data hold, auto power off, input alert, CE/UL certified, three year warranty
MIS-MTR-008	Extech AC/DC clamp-on meter, maximum AC current of 600A, measures AC current, AC/DC voltage and resistance, data hold "freezes" data in display, 33 mm jaw opening for large cables, peak hold captures in-rush currents, audible continuity beeper, auto power off, true RMS voltage and current measurements, AC/DC current to 600A, large 4000 count LCD display, capacitance and temperature measurements, includes test leads, 9V battery, carrying case and temperature probe

